

Operational Parameters 004.4/2018/ standard windows

1. Product type identification code: **04 – ENCORE.**
 2. Intended use: Windows and balcony doors to be installed in residential and commercial buildings.
 3. Producer: DOBROPLAST Fabryka Okien Sp. z o.o., Stary Laskowiec 4, 18-300 Zambrów.
 4. System of assessment and verification of constancy of performance: AoC 3 System.
 5. Harmonised standard: EN 14351-1:2006+A1:2010.
- Notified bodies: Mobilne Laboratorium Techniki Budowlanej NB 2189; Centrum Stavebnih Inženyrstvi NB 1390.

Characteristics	parameters
Wind resistance (single windows/single balcony doors)	Class C4
Wind resistance (double sash balcony doors)	Class C1,
Wind resistance (double, triple, and quadraple sash windows)	Class C4
Wind resistance (multiple sash windows)	Class C1,
Wind resistance (sliding windows)	Class C1,
Waterproofness	Class 5A
Air permeability	Class 4
Load bearing capacity of safety devices	350 N
Sound reduction (tabular); windows/balcony doors, 3/18/3/20/3 glass	maxRw=33(-1;-6)dB
Thermal transmittance: windows/balcony doors, 3/18/3/20/3 glass, Ug=0,50 W/m²K (calculatingly, EN ISO 10077-1)	Uw ≤ 1,1 W/m²K
Hazardous materials – product meets the requirements of norm EN 14351-1:2006+A1:2010 in accordance with EC Regulation (EC) No 1907/2006 (REACH), Art. 33	

Signed on behalf of producer by:
Jerzy Chrzanowski

Stary Laskowiec, 06.12.2018



DOBROPLAST
FABRYKA OKIEN sp. z o.o.
STARY LASKOWIEC 4, 18-300 Zambrów
KRS 0000404303 Regon 145908247
NIP 5252523303
tel. +48 86 276 35 50. fax +48 85 674 32 55